



# TRIPOD

## HEAVY DUTY SERIES

HDT Series Heavy Duty Tripods are designed for heavy load applications up to 300 kg, where stability and torsional strength are important.

HDT Series Heavy Duty Tripods have 8 different model options according to height, head and leg material types. They acquire fixing features to different surfaces with their standard flat and fixing perforated feet .

### FEATURES

- Professional tripods designed for heavy loads up to 300 Kg.
- Extraordinary sturdy construction.
- Extra high torsional strength.
- Suitable for indoor and outdoor use.
- Man portable and easy deployment.
- Wide working height range.
- Coating resistant to harsh conditions.
- 100% CNC Machined from high strength 6000 series aluminum and stainless steel.
- Adjustable flat feet with rubber pad and pinning holes.
- Easy column lock.
- Spirit level for easy leveling.



Product Number	Max. Height	Min. Height	Weight	Load Capacity	Stowed Dimensions	Interface	Height	Head	Legs
TS-HDT-SF-AL	990 mm	630 mm	15.9 Kg	300 Kg	ø335mm, 710mm	6xM5 thread at Ø102 mm, 6xM8 thread at Ø89 mm	Short	Fixed	Aluminum
TS-HDT-SF-CF	990 mm	630 mm	14.5 Kg	300 Kg	ø335mm, 710mm	6xM5 thread at Ø102 mm, 6xM8 thread at Ø89 mm	Short	Fixed	Carbon Fiber
TS-HDT-SA-AL	1400 mm	780 mm	20.2 Kg	250 Kg	ø335mm, 860mm	3½"-8 thread	Short	Adjustable	Aluminum
TS-HDT-SA-CF	1400 mm	780 mm	18.7 Kg	250 Kg	ø335mm, 860mm	3½"-8 thread	Short	Adjustable	Carbon Fiber
TS-HDT-TF-AL	1290 mm	925 mm	19.4 Kg	300 Kg	ø335mm, 1045mm	6xM5 thread at Ø102 mm, 6xM8 thread at Ø89 mm	Tall	Fixed	Aluminum
TS-HDT-TF-CF	1290 mm	925 mm	16.6 Kg	300 Kg	ø335mm, 1045mm	6xM5 thread at Ø102 mm, 6xM8 thread at Ø89 mm	Tall	Fixed	Carbon Fiber
TS-HDT-TA-AL	1850 mm	1060 mm	24.5 Kg	250 Kg	ø335mm, 1180mm	3½"-8 thread	Tall	Adjustable	Aluminum
TS-HDT-TA-CF	1850 mm	1060 mm	21.7 Kg	250 Kg	ø335mm, 1180mm	3½"-8 thread	Tall	Adjustable	Carbon Fiber