



TRIPOD

LIGHT DUTY SERIES

LDT Series Light Duty Tripods designed to meet the requirements in applications where weight, portability and durability are important. They are balanced tripod platforms that allow easy and fast assembly of devices with a suitable interface. The robust construction of Light Duty Tripods made them ideal for a wide range of general purpose support applications.

FEATURES

- Lightweight, robust and compact design.
- It can be transported and installed quickly by a single person.
- 10 layer carbon fiber winding pipes with models that have carbon fiber legs.
- Independently adjustable leg angles and lengths.
- 3 different pre-set leg angles that can be adjusted by finger for fast installation.
- Superior strength and stability with 34mm diameter aluminum and 10x layer carbon fiber upper legs.
- Aluminum twist lock lock structure.
- Hard black anodized coating.

LDT series tripods with 12 different model options according to center types, leg material and leg section numbers gain fixing features according to different surface types with suitable foot accessories.

Product Number	Max. Height	Min. Height	Weight	Load Capacity	Stowed Dimensions	Interface	Center	Leg Material	Leg Section
TS-TR342-CC-AL	1080 mm	135 mm	2.8 Kg	50 Kg	ø190 mm, 675 mm	5/8 "11 UNC draw bolt	Center Column	Aluminum	2
TS-TR343-CC-AL	1500 mm	140 mm	3.4 Kg	50Kg	ø190 mm, 720 mm	5/8 "11 UNC draw bolt	Center Column	Aluminum	3
TS-TR344-CC-AL	2000 mm	145 mm	3.9 Kg	40 Kg	ø190 mm, 775 mm	5/8 "11 UNC draw bolt	Center Column	Aluminum	4
TS-TR342-CC-CF	1080 mm	135 mm	2.4 Kg	50 Kg	ø190 mm, 675 mm	5/8 "11 UNC draw bolt	Center Column	Carbon Fiber	2
TS-TR343-CC-CF	1500 mm	140 mm	2.9 Kg	50Kg	ø190 mm, 720 mm	5/8 "11 UNC draw bolt	Center Column	Carbon Fiber	3
TS-TR344-CC-CF	2000 mm	145 mm	3.3 Kg	40 Kg	ø190 mm, 775 mm	5/8 "11 UNC draw bolt	Center Column	Carbon Fiber	4
TS-TR342-AC-AL	1500 mm	600 mm	3 Kg	30 Kg	ø190mm, 715 mm	3/8"-16 UNC thread	Adjustable Center Column	Aluminum	2
TS-TR343-AC-AL	2000 mm	605 mm	3.6 Kg	30 Kg	ø190mm, 770 mm	3/8"-16 UNC thread	Adjustable Center Column	Aluminum	3
TS-TR344-AC-AL	2500 mm	610 mm	4.1 Kg	30 Kg	ø190mm, 815 mm	3/8"-16 UNC thread	Adjustable Center Column	Aluminum	4
TS-TR342-AC-CF	1500 mm	600 mm	2.6 Kg	30 Kg	ø190mm, 715 mm	3/8"-16 UNC thread	Adjustable Center Column	Carbon Fiber	2
TS-TR343-AC-CF	2000 mm	605 mm	3 Kg	30 Kg	ø190mm, 770 mm	3/8"-16 UNC thread	Adjustable Center Column	Carbon Fiber	3
TS-TR344-AC-CF	2500 mm	610 mm	3.4 Kg	30 Kg	ø190mm, 815 mm	3/8"-16 UNC thread	Adjustable Center Column	Carbon Fiber	4